


CERTIFICATE OF CONFORMITY

Issued to: Huawei Digital Power Technologies Co., Ltd.
Office 01, 39th Floor, Block A, Antuoshan Headquarters Towers, 33 Antuoshan 6th Road, Futian District, Shenzhen, 518043 Guangdong, P.R. China

For the product: SOLAR INVERTER

Trade name: 
HUAWEI

Type/Model: SUN2000-12KTL-M5, SUN2000-15KTL-M5, SUN2000-17KTL-M5,
SUN2000-20KTL-M5, SUN2000-25KTL-M5, SUN2000-25K-MB0, SUN2000-20K-MB0,
SUN2000-17K-MB0, SUN2000-15K-MB0, SUN2000-12K-MB0, SUN5000-17K-MB0,
SUN5000-25K-MB0

Ratings: See Annex

Manufactured by: Huawei Digital Power Technologies Co., Ltd.
Office 01, 39th Floor, Block A, Antuoshan Headquarters Towers, 33 Antuoshan 6th Road, Futian District, Shenzhen, 518043 Guangdong, P.R. China

Requirements: NRS 097-2-1:2017 (Edition 2.1 July 2020)

This Test Certificate is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6181182.51

The examination has been carried out on one single specimen of the product. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This Test Certificate expires at the latest on 6 June 2029 or expires upon withdrawal of one of the above mentioned standards.

Shanghai, 6 June 2024

Number: 6181182.02COC

DEKRA Testing and Certification (Shanghai) Ltd.



Cliff Lin
Certification Manager

© Integral publication of this certificate and adjoining reports is allowed



DEKRA Testing and Certification (Shanghai) Ltd.

No.250, Jiangchangsang Road, Jing'an District, Shanghai, 200436 People's Republic of China

T +86 21 6056 7600 F +86 21 6056 7555 www.dekra-product-safety.com

ESA-CER-F021 v4.1

Ratings of the test product:

Operating temperature range: - 25°C to + 60°C

Protective class: I

Ingress protection rating: IP66

Power factor range (adjustable): 0.8 leading...0.8 lagging

SUN2000-12KTL-M5:

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc, max 30 A/30 A, I_{sc} PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 12 kVA, max apparent power 13.2 kVA, rated current: 18.2 A (380 Vac), 17.3 A (400 Vac), 16.7 A (415 Vac), max current: 20.2 A (380 Vac), 19.1 A (400 Vac), 18.5 A (415 Vac)

SUN2000-12K-MB0:

Battery normal voltage: 600Vdc, Battery voltage range: 600-980Vdc,

Battery maximum current: 26.25 Adc/26.25 Adc, Battery type: Li-ion

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc, max 30 A/30 A, I_{sc} PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 12 kVA, max apparent power 13.2 kVA, rated current: 18.2 A (380 Vac), 17.3 A (400 Vac), 16.7 A (415 Vac), max current: 20.2 A (380 Vac), 19.1 A (400 Vac), 18.5 A (415 Vac)

SUN2000-15KTL-M5:

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc, max 30 A/30 A, I_{sc} PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 15 kVA, max apparent power 16.5 kVA, rated current: 22.8 A (380 Vac), 21.7 A (400 Vac), 20.9 A (415 Vac), max current: 25.2 A (380 Vac), 23.9 A (400 Vac), 23.1 A (415 Vac)

SUN2000-15K-MB0:

Battery normal voltage: 600Vdc, Battery voltage range: 600-980Vdc,

Battery maximum current: 26.25 Adc/26.25 Adc, Battery type: Li-ion

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc, max 30 A/30 A, I_{sc} PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 15 kVA, max apparent power 16.5 kVA, rated current: 22.8 A (380 Vac), 21.7 A (400 Vac), 20.9 A (415 Vac), max current: 25.2 A (380 Vac), 23.9 A (400 Vac), 23.1 A (415 Vac)

SUN2000-17KTL-M5:

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc, max 30 A/30 A, I_{sc} PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 17 kVA, max apparent power 18.7 kVA, rated current: 25.8 A (380 Vac), 24.5 A (400 Vac), 23.7 A (415 Vac), max current: 28.6 A (380 Vac), 27.1 A (400 Vac), 26.1 A (415 Vac)

SUN2000-17K-MB0:

Battery normal voltage: 600Vdc, Battery voltage range: 600-980Vdc,

Battery maximum current: 26.25 Adc/26.25 Adc, Battery type: Li-ion

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc, max 30 A/30 A, I_{sc} PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 17 kVA, max apparent power 18.7 kVA, rated current: 25.8 A (380 Vac), 24.5 A (400 Vac), 23.7 A (415 Vac), max current: 28.6 A (380 Vac), 27.1 A (400 Vac), 26.1 A (415 Vac)

SUN2000-20KTL-M5:

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc, max 30 A/30 A, I_{sc} PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 20 kVA, max apparent power 22 kVA, rated current: 30.4 A (380 Vac), 28.9 A (400 Vac), 27.8 A (415 Vac), max current: 33.6 A (380 Vac), 31.9 A (400 Vac), 30.8 A (415 Vac)

SUN2000-20K-MB0:

Battery normal voltage: 600Vdc, Battery voltage range: 600-980Vdc,

Battery maximum current: 26.25 Adc/26.25 Adc, Battery type: Li-ion

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc,

max 30 A/30 A, Isc PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 20 kVA, max apparent power 22 kVA,

rated current: 30.4 A (380 Vac), 28.9 A (400 Vac), 27.8 A (415 Vac), max current: 33.6 A (380 Vac), 31.9 A (400 Vac), 30.8 A (415 Vac)

SUN2000-25KTL-M5:

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc,

max 30 A/30 A, Isc PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 25 kVA, max

apparent power 27.5 kVA, rated current: 38.0 A (380 Vac), 36.1 A (400 Vac), 34.8 A (415 Vac), max current: 42.0 A (380 Vac), 39.9 A (400 Vac), 38.5 A (415 Vac)

SUN2000-25K-MB0:

Battery normal voltage: 600Vdc, Battery voltage range: 600-980Vdc,

Battery maximum current: 26.25 Adc/26.25 Adc, Battery type: Li-ion

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc,

max 30 A/30 A, Isc PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 25 kVA, max

apparent power 27.5 kVA, rated current: 38.0 A (380 Vac), 36.1 A (400 Vac), 34.8 A (415 Vac), max current: 42.0 A (380 Vac), 39.9 A (400 Vac), 38.5 A (415 Vac)

SUN5000-17K-MB0:

Battery normal voltage: 600Vdc, Battery voltage range: 600-980Vdc,

Battery maximum current: 26.25 Adc/26.25 Adc, Battery type: Li-ion

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc,

max 30 A/30 A, Isc PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 17 kVA, max

apparent power 18.7 kVA, rated current: 25.8 A (380 Vac), 24.5 A (400 Vac), 23.7 A (415 Vac), max current: 28.6 A (380 Vac), 27.1 A (400 Vac), 26.1 A (415 Vac)

SUN5000-25K-MB0:

Battery normal voltage: 600Vdc, Battery voltage range: 600-980Vdc,

Battery maximum current: 26.25 Adc/26.25 Adc, Battery type: Li-ion

PV input: max 1100 Vdc, MPPT voltage range: 200–1000 Vdc,

max 30 A/30 A, Isc PV: 40 A/40 A

AC output: 3/N/PE, 220/380 Vac, 230/400 Vac, 240/415 Vac, 50 Hz, rated apparent power 25 kVA, max

apparent power 27.5 kVA, rated current: 38.0 A (380 Vac), 36.1 A (400 Vac), 34.8 A (415 Vac), max current: 42.0 A (380 Vac), 39.9 A (400 Vac), 38.5 A (415 Vac)

--END--